



ABM&AFM SERIES

THE BENCH & FLOOR SCALE





ABM&AFM

COMMON FEATURES

- OIML-R76 and EC Class III Type Approved
- Flexible Platform Collocation
- Designed to Meet Industrial Application Requirements
- Mold Injected Aluminum Alloy Platform
- Stainless Steel Platform Cover
- Overload Protection Devices Against Excessive Load or Shock Applied
- Equipped with Power On Zero Tracking, Re-zero, Auto Calibration, Auto Power Saving, Digital Motion Filtering Device, Auto Tare, Accumulation Memory and Dual Interval Selection**
- Dual Power Source: By Built-in Rechargeable Battery or Power Adaptor
- Long Battery Operating Time:
ABM: 150 Hours Plus
AFM: 200 Hours Plus
- Complete with Low Battery and Charging Status Indicator
- 5 1/2 x 51mm Oversize Wide Angle LCD Digits
- Adjustable Feet, Rechargeable Battery, Power Adaptor, Bubble Level and Indicator Dust Cover Included

**Depends on R60 approval grade of the load cell used

DISPLAY RESOLUTION: - OIML APPLICATIONS

- Standard = 3000
- Maximum = 30000 Under Extended Display Mode

DISPLAY RESOLUTION: - NON-OIML APPLICATIONS

- User Programmable
- Recommended = 6000 to 7500
- Maximum = 30000

OPTION AVAILABLE

- EL Backlight
- Printer or RS232C Interface Output

SPECIFICATIONS

Model No.	Capacity	Recommended Display Resolution		Platform	Individual Package
		OIML Application	Non-OIML Application		
ABM-30	30kg	0.01kg	0.005kg	330 x 450mm with Stainless Steel Cover	580(L) x 410(W) x 290(H)mm Net/Gross Weight: 11/12.6kg
ABM-60	60kg	0.02kg	0.01kg		
ABM-150	150kg	0.05kg	0.02kg		
AFM-F60	60kg	0.02kg	0.01kg	420 x 520mm with Stainless Steel Cover	880(L) x 640(W) x 210(H)mm Net/Gross Weight: 19.6/22.5kg
AFM-F150	150kg	0.05kg	0.02kg		
AFM-F300	300kg	0.1kg	0.05kg		
AFM-L150	150kg	0.05kg	0.02kg	500 x 600mm with Stainless Steel Cover	880(L) x 640(W) x 210(H)mm Net/Gross Weight: 26.8/29.7kg
AFM-L300	300kg	0.01kg	0.005kg		
AFM-L550	550kg	0.2kg	0.1kg		
Tare Range	OIML = 1/3 Max. - e Non-OIML = Full Range				
Power Source	By Built-in Rechargeable Battery or AC/DC Power Adaptor				
Operating Environment	0° - 40°C (32° - 104°F), Non-condensed R.H. ≤ 85%				

Specifications subject to change without notice



UNIVERSAL WEIGHT ENTERPRISE CO., LTD.

2-5 Floor No. 39 Pao Shing Road Hsin Tien City 231 Taipei Hsien Taiwan R.O.C.
Tel: +886-2-29180121 (12 Lines) Fax: +886-2-29181508-29183652-29112176-7
http://www.uwe-scale.com.tw e-mail: uwe@ms8.hinet.net

Oct '2002 Designed by DALY
Printed in Taiwan